

# SA PU MAINTENANCE KIT

## USER MANUAL + TECHNICAL DATASHEET

### PRODUCT DESCRIPTION

SA PU Maintenance Kit is a maintenance set especially for the daily maintenance and protection of Stone Age products finished with 2K-PU.

### USAGE

The following maintenance products have been developed especially for Stone Age products finished with 2K-PU:

- SA PU Cleaner: for daily cleaning of Stone Age products finished with 2K-PU.
- SA PU Protect Mat: for maintenance/protection of Stone Age products finished with 2K-PU.

### MAINTENANCE ADVICE

#### SA PU Cleaner

SA PU Cleaner is a special active cleaner for maintenance cleaning of floors and walls finished with 2K PU. The SA PU Cleaner can be used for daily maintenance. Before use the surface should be made dust-free. For this purpose remove loose dirt and soiling by sweeping or vacuuming.

Daily cleaning in the proportion of about 50 ml SA PU Cleaner to 5 liters of water and mop/polish with this solution. In case of heavy soiling dilute SA PU Cleaner up to a ratio of 1 liter to 10 liters of water.

Note: Do not allow sensitive surfaces such as wood, metal, furniture, etc. to come into contact with the cleaning solution. Suitable as a maintenance product for base concrete, concrete cure, concrete flow and oxidation plaster, finished with 2K-PU.

Frequency of use: weekly

### SA PU PROTECT MAT

SA PU Protect Mat is a special wax for the maintenance of floors and walls finished with 2K-PU. Use the SA PU Protect Mat after cleaning the floor/wall with SA PU Cleaner. The SA PU Protect Mat fills small scratches and reduces the adhesion of dirt.

Use about 25 ml of SA PU Protect Mat undiluted per m<sup>2</sup> (per quarter) for optimal protection. Optionally apply diluted with water for more frequent use, use about 50 ml SA PU Protect Mat on 5 liters of water and mop with this solution. Preferably clean the floor/wall first with SA PU Cleaner for optimal results.

Suitable as a maintenance product for base concrete, concrete cure, concrete flow and oxidation stucco, finished with 2K PU.

Frequency of use: 2-4 x per year

### TECHNICAL DATA SA PU CLEANER

SA PU Cleaner is a special cleaner suitable for daily cleaning of Stone Age floor and wall finishes finished with a SA coating.

- Excellent flow and adhesion.
- Safe to use.
- High solids content.
- Low emission (EMICODE: EC2 R).

Gloss levels: none

### USAGE

SA PU Cleaner only at a temperature of at least 15 °C on the prepared substrate (with reference to our note 'Basic cleaning of substrates')

Remark:

The substrate must be properly prepared and be in a roughened, clean, dry, oil, wax and dust-free condition.

**!! Note: After the Stone Age product has been applied to the floor, the floor - in view of the composition of the Stone Age product - may never be covered with tape afterwards (i.e. even when**

**the floor is already in use!). This will prevent possible disturbing prints, which could cause damage to the floor. Stone Age accepts no liability whatsoever for damage occurring if the floor concerned is covered with tape against this instruction.**

## **STORAGE**

Protect from frost. Store in a cool and dry place. Shelf-life A maximum of 12 months in unopened original packaging from the date of production. Keep out of the reach of children.

During storage, constrictions may arise due to fluctuations in temperature and in previously opened containers. Sieve well before use.

## **TECHNICAL VALUES**

pH value: approx. 9.5

Contents: Less than 5% a-ionic tenside, 5-15% non-ionic tenside.

Contains fragrances, solvents, conditioning agents.

GU 50

## **REFERENCES**

Our following publications, in their current form, serve as supplements to this Information Sheet:

- General Notes on the Use of Stone Age Products.
- Safety Data Sheet, which is available on request.
- Bottle labelling

The specified publications, as well as this Information Sheet in its most current form, are available at the address below:

Butaanstraat 10  
7463 PG Rijssen  
[info@stoneage.nl](mailto:info@stoneage.nl)

## **Disclaimer**

Our above-mentioned technical advice is drawn up to the best of our knowledge and based on the latest state of the art.

For this reason, when using our products, observing the application instructions given and the procedure we suggest, no damage will be caused to the materials for which these products are intended.

However, the use of our products is beyond our control, remains your own responsibility and does not relieve you of prior testing of our products for suitability for the intended procedures and purposes. Our advice and regulations are therefore not binding and cannot be invoked against us - which also applies to any property rights of third parties. The relevant recommendations, directives and standards, as well as the recognized rules from the technology must be observed. With the publication of this product information, previous versions lose their validity.

## TECHNICAL DATA SA PU PROTECT MAT

SA PU Protect is a Polyurethane containing polymer dispersion and is intended for the maintenance and protection of laid floors with 2KPU finishes.

- Excellent flow and adhesion.
- Safe to use
- High solids content.
- Low emission (EMICODE: EC2 R).

Gloss levels: matt

## USAGE

SA PU Protect Mat only at a temperature of at least 15 °C on the prepared substrate (with reference to our note 'Basic cleaning of substrates')

Remark:

The substrate must be properly prepared and be in a roughened, clean, dry, oil, wax and dust-free condition.

**!! Note: After the Stone Age product has been applied to the floor, the floor - in view of the composition of the Stone Age product - may never be covered with tape afterwards (i.e. even when the floor is already in use!). This will prevent possible disturbing prints, which could cause damage to the floor. Stone Age accepts no liability whatsoever for damage occurring if the floor concerned is covered with tape against this instruction.**

## STORAGE

Protect from frost. Store in a cool and dry place. Shelf-life A maximum of 12 months in unopened original packaging from the date of production. Keep out of the reach of children.

During storage, constrictions may arise due to fluctuations in temperature and in previously opened containers. Sieve well before use.

## TECHNICAL VALUES

pH value: approx. 8.4

Contents: Less than 5% nonionic tenside.

## Contains

CHLOROMETHYLISOTHIAZOLINONE, METHYLISOTHIAZOLINONE, BRONOPOL, fragrances, solvents, conditioning agents. GE 10

## REFERENCES

Our following publications, in their current form, serve as supplements to this Information Sheet:

- General Notes on the Use of Stone Age Products.
- Safety Data Sheet, which is available on request.
- Bottle labelling

The specified publications, as well as this Information Sheet in its most current form, are available at the address below:

**STONE AGE**  
READY TO CREATE

Butaanstraat 10  
7463 PG Rijssen  
[info@stoneage.nl](mailto:info@stoneage.nl)

## DISCLAIMER

Our above-mentioned technical advice is drawn up to the best of our knowledge and based on the latest state of the art. For this reason, when using our products, observing the application instructions given and the procedure we suggest, no damage will be caused to the materials for which these products are intended.

However, the use of our products is beyond our control, remains your own responsibility and does not relieve you of prior testing of our products for suitability for the intended procedures and purposes. Our advice and regulations are therefore not binding and cannot be invoked against us - which also applies to any property rights of third parties. The relevant recommendations, directives and standards, as well as the recognized rules from the technology must be observed. With the publication of this

product information, previous versions lose their validity.

## **MAINTENANCE TIPS**

### **Tips for preventive maintenance and avoiding damage**

- Prevention is better than cure. Everyone who walks into your home takes a piece of the "outside world" with them through their shoe soles. By using a good entrance mat or clean walking zone, you can largely prevent dirt and moisture from entering your home.

Stone Age floor less often and prolong its life.

- Do not slide heavy objects across the floor and provide chair legs and other furniture with good protection (see [www.scratchnomore.com](http://www.scratchnomore.com)).

- If necessary, replace the wheels under the office chairs with soft wheels.

- Remove spilled liquids as soon as possible.

### **Avoid discoloration:**

Every floor covering discolours under the influence of sunlight. Although your floor is a UV stable floor, it will also discolour slightly after years (this is also the case with wood, vinyl or carpet). This is due to the ultraviolet radiation in sunlight. To prevent discoloration of your floor, it is important to apply good sun protection.

### **Avoid contact with rubber:**

Contact between rubber and the SA Master PU top layer should be avoided as much as possible. In case of prolonged contact between the SA Master PU top coat and rubber, a permanent, dark brown discoloration may occur due to migration (think of a rubber ring under a trash can, rubber cleaning mats, placemats, etc.). Rubber caps under furniture can also cause streaks due to friction. We therefore recommend that you check all your furniture and utensils for rubber caps and provide them with protection (see [www.scratchnomore.com](http://www.scratchnomore.com)).