

SA FIX PRIMER

USER MANUAL + TECHNICAL DATASHEET

PRODUCT DESCRIPTION:

Single-component, ready-to-use water-based adhesion primer

SA Fix Primer is a high-quality, water-based primer with fine aggregates, specially developed to stabilise substrates and fix reinforcement mesh on interior surfaces such as concrete, cement, plaster, plasterboard, wood, and ceramic tiles. Suitable for both horizontal and vertical applications, it provides a strong bonding base and regulates absorption for optimal surface preparation.

USAGE

Shake well before use. Ensure the surface is clean, dry, and free from dust, oil, grease, wax, or any loose or non-adhering materials. Remove residues of previous coatings and thoroughly sand anhydrite screeds before application. Surfaces such as parquet, resilient floors, or tiles must be stripped of any waxes or release agents. Make sure no rising damp is present in the substrate.

Apply SA Fix Primer evenly using a roller or brush. On highly absorbent substrates such as screeds or plaster, apply a first diluted coat (approx. 20% water) to regulate absorption, followed by a second undiluted coat while embedding the fibre mesh.

During mesh installation, avoid overlaps or folds—do not overlap mesh at the joints.

SA Fix Primer can also be used directly on indoor ceramic tiles (walls and floors) and as a vertical primer for plasterboard or civil plaster. On very smooth surfaces, dilute the product by 5–10% with water to improve workability.

SA Fix Primer only at a temperature of at least 15 °C on the prepared substrate (with reference to our note 'Basic cleaning of substrates')

Remark:

The substrate must be properly prepared and be in a roughened, clean, dry, oil, wax and dust-free condition.

!! Note: After the Stone Age product has been applied to the floor, the floor - in view of the composition of the Stone Age product - may never be covered with tape afterwards (i.e. even when the floor is already in use!). This will prevent possible disturbing prints, which could cause damage to the floor. Stone Age accepts no liability whatsoever for damage occurring if the floor concerned is covered with tape against this instruction.

STORAGE

Protect from frost. Store in a cool and dry place. Shelf-life A maximum of 12 months in unopened original packaging from the date of production. Keep out of the reach of children.

During storage, constrictions may arise due to fluctuations in temperature and in previously opened containers. Sieve well before use.

TECHNICAL VALUES

pH value: approx. 9.5

Contents: Less than 5% a-ionic tenside, 5-15% non-ionic tenside.
Contains fragrances, solvents, conditioning agents.
GU 50

REFERENCES

Our following publications, in their current form, serve as supplements to this Information Sheet:

- General Notes on the Use of Stone Age Products.
- Safety Data Sheet, which is available on request.
- Bottle labelling

The specified publications, as well as this Information Sheet in its most current form, are available at the address below:



Butaanstraat 10
7463 PG Rijssen
info@stoneage.nl

Disclaimer

Our above-mentioned technical advice is drawn up to the best of our knowledge and based on the latest state of the art. For this reason, when using our products, observing the application instructions given and the procedure we suggest, no damage will be caused to the materials for which these products are intended.

However, the use of our products is beyond our control, remains your own responsibility and does not relieve you of prior testing of our products for suitability for the intended procedures and purposes. Our advice and regulations are therefore not binding and cannot be invoked against us - which also applies to any property rights of third parties. The relevant recommendations, directives and standards, as well as the recognized rules from the technology must be observed. With the publication of this product information, previous versions lose their validity.