

VRPM000XPSTA0010 - SA PU PROTECT MATTE

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: VRPM000XPSTA0010
Product name: SA PU PROTECT MATTE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Protective for the extraordinary maintenance of resin and resilient floors

Identified Uses	Industrial	Professional	Consumer
Floor maintenance	✓	✓	✓

1.3. Details of the supplier of the safety data sheet

Name: Stone Age B.V.
Full address: Butaanstraat 10
District and Country: 7463PG RIJSEN (OV)
NETHERLANDS
Tel.: +31 548 544 449

e-mail address of the competent person responsible for the Safety Data Sheet

info@stoneage.nl

1.4. Emergency telephone number

For urgent inquiries refer to

Poison centers:
Cyprus-1401

Denmark- Danish Poison Center (Giftlinjen): +45 8212 1212

Estonia- Estonian Poisoning Information 16662

Finland- Tel. 09 471 977 Or +358 09 4711

Latvia- 1. Valsts ugunsdzēsības un glābšanas dienests, phone number: 112.
2. Toksikoloģijas un sepses klīnikas Saindēšanās un zāļu informācijas centrs,
Hipokrāta 2, Rīga, Latvija, LV-1038, phone number +371 67042473

Lithuania- Apsinuodijimų informacijos biuras"visto paraž: tel. +370 (5) 236 2052

Malta- 112

Belgium
Belgian Poisono Centre number: 070 245 245
Available 24h/24

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to (EU) Regulation 2020/878.

Hazard classification and indication: --

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

VRPM000XPSTA0010 - SA PU PROTECT MATTE

SECTION 2. Hazards identification ... / >>

Hazard pictograms: --

Signal words: --

Hazard statements:

EUH210

Safety data sheet available on request.

EUH208

Contains: Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)
1,2-BENZISOTHIAZOLINE 3 (2H) -ONE
2,4,7,9-tetramethyldec-5-yne-4,7-diol
Adipohydrazide
May produce an allergic reaction.

Precautionary statements: --

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
2-(2-butoxyethoxy)ethanol		
INDEX 603-096-00-8	3 ≤ x < 6	Eye Irrit. 2 H319
EC 203-961-6		
CAS 112-34-5		
REACH Reg. 01-2119475104-44-XXXX		
Adipohydrazide		
INDEX 213-999-5	0 < x < 0,5	Skin Sens. 1 H317, Aquatic Chronic 2 H411
EC 1071-93-8		
CAS 1071-93-8		
REACH Reg. 01-2119962900-36-xxxx		
2,4,7,9-tetramethyldec-5-yne-4,7-diol		
INDEX 204-809-1	0 < x < 0,5	Eye Dam. 1 H318, Skin Sens. 1B H317, Aquatic Chronic 3 H412
EC 126-86-3		
CAS 126-86-3		
REACH Reg. 01-2119954390-39-XXXX		
1,2-BENZISOTHIAZOLINE 3 (2H) -ONE		
INDEX 613-088-00-6	0 < x < 0,05	Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411 Skin Sens. 1 H317: \geq 0,05% ATE Oral: 500 mg/kg
EC 220-120-9		
CAS 2634-33-5		
REACH Reg. 01-2120761540-60		
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)		
INDEX 613-167-00-5	0 < x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1C H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, EUH071 Skin Corr. 1C H314: \geq 0,6%, Skin Irrit. 2 H315: \geq 0,06% - < 0,6%, Skin Sens. 1A H317: \geq 0,0015%, Eye Dam. 1 H318: \geq 0,6% LD50 Oral: 64 mg/kg, LD50 Dermal: 87 mg/kg, ATE Inhalation vapours: 0,501 mg/l
EC 911-418-6		
CAS 55965-84-9		
REACH Reg. 01-2120764691-48-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 4. First aid measures****4.1. Description of first aid measures**

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice.

Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 6. Accidental release measures** ... / >>

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France Décret n° 2021-1849 du 28 décembre 2021
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych

VRPM000XPSTA0010 - SA PU PROTECT MATTE

SECTION 8. Exposure controls/personal protection ... / >>

ROU	România	dla zdravia w środowisku pracy Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК) ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

2-(2-butoxyethoxy)ethanol

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	67,5	10	101,2	15	
TLV	CZE	70	10,36	100	14,8	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
VLA	ESP	67,5	10	101,2	15	
VLEP	FRA	67,5	10	101,2	15	
TLV	GRC	67,5	10	101,2	15	
AK	HUN	67,5	10	101,2	15	
VLEP	ITA	67,5	10	101,2	15	
TLV	NOR	68	10			
TGG	NLD	50		100		SKIN
VLE	PRT	67,5	10	101,2	15	
NDS/NDSch	POL	67		100		
TLV	ROU	67,5	10	101,2	15	
ПДК	RUS			5		n
NGV/KGV	SWE	68	10	101	15	
NPEL	SVK	67,5	10	101,2	15	
MV	SVN	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			INHAL

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,1	mg/l
Normal value in marine water	11	mg/l
Normal value for fresh water sediment	4,4	mg/kg
Normal value for marine water sediment	440	µg/kg
Normal value for marine water, intermittent release	110	µg/L
Normal value of STP microorganisms	NPI	
Normal value for the food chain (secondary poisoning)	56	mg/kg
Normal value for the terrestrial compartment	320	µg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		6,25 mg/kg				
Inhalation		NPI	LOW	NPI	101,2 mg/m ³	NPI	67,5 mg/m ³	NPI
Skin		NPI	NPI	NPI	NPI	NPI	LOW	NPI

VRPM000XPSTA0010 - SA PU PROTECT MATTE

SECTION 8. Exposure controls/personal protection ... / >>

Adipohydrazide

Predicted no-effect concentration - PNEC

Normal value in fresh water	62	µg/L
Normal value in marine water	92	µg/L
Normal value for fresh water sediment	241	µg/kg
Normal value for marine water sediment	24,1	µg/kg
Normal value for marine water, intermittent release	6,2	µg/L
Normal value of STP microorganisms	1	g/l
Normal value for the terrestrial compartment	11,8	µg/kg
Normal value for the atmosphere	NPI	

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		NPI		NPI				
Inhalation		NPI	NPI	NPI	NPI	NPI	NPI	17,5 mg/m ³
Skin		NPI	NPI	NPI	NPI	NPI	NPI	NPI

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,339	mg/l
Normal value in marine water	0,339	mg/l
Normal value for fresh water sediment	0,027	mg/kg/d
Normal value for marine water sediment	0,027	mg/kg/d
Normal value of STP microorganisms	0,23	mg/l
Normal value for the terrestrial compartment	0,01	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		0,11 mg/kg bw/d		0,09 mg/kg bw/d				
Inhalation	0,04 mg/m ³		0,02 mg/m ³		0,04 mg/m ³		0,02 mg/m ³	

1,2-BENZISOTHIAZOLINE 3 (2H) -ONE

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00403	mg/l
Normal value in marine water	0,00040	mg/l
Normal value for fresh water sediment	3	
Normal value for marine water sediment	0,0499	mg/kg
Normal value of STP microorganisms	0,499	mg/kg
Normal value for the terrestrial compartment	1,03	mg/l
Normal value for the atmosphere	3	mg/kg/d

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,2 mg/m ³				6,81 mg/m ³
Skin				0,345 mg/kg bw/d				0,966 mg/kg bw/d

VRPM000XPSTA0010 - SA PU PROTECT MATTE

SECTION 8. Exposure controls/personal protection ... / >>

2,4,7,9-tetramethyldec-5-yne-4,7-diol

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,04	mg/l
Normal value in marine water	0,004	mg/l
Normal value for fresh water sediment	0,32	mg/kg/d
Normal value for marine water sediment	0,032	mg/kg/d
Normal value for water, intermittent release	0,4	mg/l
Normal value of STP microorganisms	7	mg/l
Normal value for the terrestrial compartment	0,028	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			0,75 mg/kg bw/d	0,25 mg/kg bw/d				
Inhalation			1,29 mg/m3	0,43 mg/m3			5,28 mg/m3	1,76 mg/m3
Skin			0,75 mg/kg bw/d	0,25 mg/kg bw/d			1,5 mg/kg/d	0,5 mg/kg/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	characteristic	
Melting point / freezing point	not available	Reason for missing data:Date not available
Initial boiling point	100 °C	Method:Bibliography relating to the most relevant component of the preparation
Flammability	not available	Reason for missing data:Date not available
Lower explosive limit	not available	Reason for missing data:Date not available
Upper explosive limit	not available	Reason for missing data:Date not available
Flash point	> 60 °C	Method:Internal evaluation, The determination of the flash point of the products is carried out

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 9. Physical and chemical properties** ... / >>

Auto-ignition temperature	not available	through the evaluation of the components relevant to this category of danger, the value of the flash point corresponds to the lowest value among these components that follow the determination of the flash point via EN ISO 2719 Reason for missing data:Date not available Reason for missing data:Date not available Method:ISO 976 Method:Calculated from the Dynamic Viscosity value Method:Bibliography relating to the most relevant component of the preparation Reason for missing data:Date not available Reason for missing data:data: product not subject to melting by heating. Method:UNI EN ISO 2811-1 Reason for missing data:Date not available
Decomposition temperature	not available	
pH	8	
Kinematic viscosity	15 - 20 mm ² /s	
Dynamic viscosity	10 - 30 DIN 4	
Solubility	partially soluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	not available	
Density and/or relative density	1,01 kg/l	
Relative vapour density	not available	
Particle characteristics	not applicable	

Supplementary information for nanoforms**Shape****Shape 1:**

Shape name	The structure of synthetic amorphous silicon (SAS) can
Category	spheroidal
Shape	spherical
Aspect ration (x:1)	CATEG :1
D50	

Crystallinity**Crystalline structure 1:**

Structure	amorphous
-----------	-----------

Surface functionalisation / treatment**Surface treatments 1:**

Surface treatment applied	no
---------------------------	----

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	3,00 % - 30,30	g/litre
VOC (volatile carbon)	< 0.01 % - < 0.01	g/litre

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 10. Stability and reactivity** ... / >>

2-(2-butoxyethoxy)ethanol

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-(2-butoxyethoxy)ethanol

Avoid exposure to: air.

10.5. Incompatible materials

2-(2-butoxyethoxy)ethanol

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products

2-(2-butoxyethoxy)ethanol

May develop: hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

2-(2-butoxyethoxy)ethanol

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-butoxyethoxy)ethanol

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

2-(2-butoxyethoxy)ethanol

LD50 (Dermal):

2764 mg/kg (rabbit)

LD50 (Oral):

2410 mg/kg (mouse)

Adipohydrazide

LD50 (Oral):

2000 mg/kg (rat)

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)

LD50 (Dermal):

87 mg/kg Ratto

LD50 (Oral):

64 mg/kg Ratto

LC50 (Inhalation vapours):

330 mg/m³ 4h Ratto

1,2-BENZISOTHIAZOLINE 3 (2H) -ONE

LD50 (Dermal):

> 2000 mg/kg Ratto

LD50 (Oral):

784 mg/kg Female Rat

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 11. Toxicological information ... / >>**

2,4,7,9-tetramethyldec-5-yne-4,7-diol
LD50 (Dermal): > 2000 mg/kg Ratto
LD50 (Oral): > 2000 mg/kg Ratto

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)

1,2-BENZISOTHIAZOLINE 3 (2H) -ONE

2,4,7,9-tetramethyldec-5-yne-4,7-diol

Adipohydrazide

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2-(2-butoxyethoxy)ethanol
LC50 - for Fish 1,3 g/L/96h
EC50 - for Crustacea 100 mg/l/48h
EC50 - for Algae / Aquatic Plants 1,101 g/L/72h
Chronic NOEC for Algae / Aquatic Plants 100 mg/l

Adipohydrazide
LC50 - for Fish 100 mg/l/96h
EC50 - for Crustacea 106 mg/l/48h
EC50 - for Algae / Aquatic Plants > 3,94 mg/l/72h
EC10 for Crustacea 106 mg/l/48h
EC10 for Algae / Aquatic Plants 3,11 mg/l/72h

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 12. Ecological information ... / >>**

Chronic NOEC for Algae / Aquatic Plants	1,97 mg/l
Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)	
LC50 - for Fish	0,19 mg/l/96h Pesce Oncorhynchus mykiss
EC50 - for Crustacea	0,16 mg/l/48h Dafnia
EC50 - for Algae / Aquatic Plants	0,037 mg/l/72h Alge - Selenastrum capricornutum
Chronic NOEC for Fish	0,02 mg/l
Chronic NOEC for Crustacea	0,1 mg/l
1,2-BENZISOTHIAZOLINE 3 (2H) -ONE	
LC50 - for Fish	2,15 mg/l/96h
EC50 - for Crustacea	2,94 mg/l/48h
EC50 - for Algae / Aquatic Plants	0,11 mg/l/72h
2,4,7,9-tetramethyldec-5-yne-4,7-diol	
LC50 - for Fish	36 mg/l/96h Pimephales promelas
EC50 - for Crustacea	91 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	82 mg/l/72h Pseudokirchneriella subcapitata

12.2. Persistence and degradability

2-(2-butoxyethoxy)ethanol	
Solubility in water	955 g/l
Rapidly degradable	
Adipohydrazide	
Solubility in water	102 g/l
Rapidly degradable	

Mixture of: 5-chloro-2-methyl-2H-isothiazol-3-one; 2-methyl-2H-isothiazol-3-one (3: 1)
Entirely degradable

12.3. Bioaccumulative potential

2-(2-butoxyethoxy)ethanol	
Partition coefficient: n-octanol/water	1
Adipohydrazide	
Partition coefficient: n-octanol/water	-2,7
1,2-BENZISOTHIAZOLINE 3 (2H) -ONE	
Partition coefficient: n-octanol/water	0,7

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 15. Regulatory information ... / >>**

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1C	Skin corrosion, category 1C
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Skin Sens. 1A	Skin sensitization, category 1A
Skin Sens. 1B	Skin sensitization, category 1B
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H310	Fatal in contact with skin.
H330	Fatal if inhaled.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH210	Safety data sheet available on request.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals

VRPM000XPSTA0010 - SA PU PROTECT MATTE**SECTION 16. Other information ... / >>**

- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
24. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

VRPM000XPSTA0010 - SA PU PROTECT MATTE

SECTION 16. Other information ... / >>

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 08 / 09 / 11 / 12 / 15 / 16.